

WHAT IS CLAIMED IS:

1. A cable lock comprising a body, a key hole formed in a lower side of said body, a fix hole and an insert hole formed spaced apart in an upper side of said body, a cable connected with said body and being
5 flexible to bend freely; and,

characterized by said body having a vertical side bored with a pin hole communicating with said fix hole for a pin to fit firmly therein, plural metal rings connected with one another to form a tubular cover which fits around said cable, each said ring having one end formed with a round
10 projection and the other end formed with a curved recess, said round projection of one said ring engaging with said curved recess of another said ring to allow said plural metal rings connected with one to form said tubular cover; a fix bolt attached with one end of said cable, said fix bolt fixed firmly in said fix hole of said body and having a hole in an upper end
15 for one end of said cable to insert therein and a curve recess formed in the other end to fit with said round projection of said metal ring, said fix bolt further having an annular groove formed in the intermediate portion; a removable bolt attached with the other end of said cable and inserting in or pulled out of said inset hole of said body, said removable bolt having a
20 round projection on an upper end to engage with said curved recess of said metal ring, said removable bolt further having an annular groove near the upper end;

said tubular cover allowing said cable to bend freely because of engagement of said round projection of one metal ring with said curved
25 recess of another said metal ring, said tubular cover increasing the strength of said cable for preventing said cable from illegally cut off by a thief so as to attain anti-theft function.